

Testing is performed at an internationally recognized, independent research, engineering and evaluation laboratory who by contractual agreement with their clients does not allow the use of their name or logo because doing so may imply an endorsement of products or services. For this reason, all references to said independent third party lab have been removed. Should you require the full unedited version, please contact the company identified below.

Mechanical Engineering Division
May 16, 2013

SUMMARY OF TESTS PERFORMED


Project Number: 18.04481.22.101

Company: Panasonic Computer Solutions Company
Three Panasonic Way, 2F-12
Secaucus, NJ 07094
Attn: Daniel Bocage

Equipment Tested: Panasonic FZ-G1 Tablet Computer

Test Dates: February 2013 – May 2013

Notes: *The test item was evaluated for ability to boot into the Windows® 8 operating system following each of the tests described within this summary report or for the ability to play an audio/visual file during the test parameter application. A listing of summarized tests and results appear in the accompanying table. Full details will be provided in Report Number 18.04481.22.100.FR1.*

Report Written By: 
Eric Dornes
Principal Engineer
Structural Dynamics and Product Assurance Section

Summary of Tests Performed on the Panasonic FZ-G1 Tablet Computer

Test Description	Test Parameters	Test Results
Altitude: Storage/Air Transport	MIL-STD-810G, Method 500.5, Procedure I <ul style="list-style-type: none"> 40,000ft Non-Operating 	Pass
Altitude: Operation/Air Carriage	MIL-STD-810G, Method 500.5, Procedure II <ul style="list-style-type: none"> 40,000ft Operating 	Pass
High Temperature: Storage	MIL-STD-810G, Method 501.5, Procedure I <ul style="list-style-type: none"> 160°F Non-Operating 	Pass
High Temperature: Operation	MIL-STD-810G, Method 501.5, Procedure II <ul style="list-style-type: none"> 140°F Operating 	Pass
High Temperature: Tactical–Standby to Operational	MIL-STD-810G, Method 501.5, Procedure III <ul style="list-style-type: none"> High storage (non-operating) to high operating (test for operation) Test results are for AC power operation 	Pass
Low Temperature: Storage	MIL-STD-810G, Method 502.5, Procedure I <ul style="list-style-type: none"> -60°F Non-Operating 	Pass
Low Temperature: Operation	MIL-STD-810G, Method 502.5, Procedure II <ul style="list-style-type: none"> -20°F Operating 	Pass
Temperature Shock	MIL-STD-810G, Method 503.5, Procedure I <ul style="list-style-type: none"> From 200°F to -60°F, three cycles 	Pass
Rain: Blowing	MIL-STD-810G, Method 506.5, Procedure I <ul style="list-style-type: none"> 5.8in/hr rain, 70mph wind, 30 minutes per surface Unit operating 	Pass
Rain: Drip	MIL-STD-810G, Method 506.5, Procedure III <ul style="list-style-type: none"> 15 minute exposure, drip test 	Pass
Humidity	MIL-STD-810G, Method 507.5, Procedure II (Aggravated) <ul style="list-style-type: none"> Temp. cycles 86°F to 140°F; 95%RH 	Pass
Sand and Dust: Dust	MIL-STD-810G, Method 510.5, Procedure I <ul style="list-style-type: none"> Blowing Dust (operating) Operating temperature of 160°F 	Pass
Sand and Dust: Sand	MIL-STD-810G, Method 510.5, Procedure II <ul style="list-style-type: none"> Blowing Sand (operating) Operating temperature of 160°F 	Pass
Explosive Atmosphere	MIL-STD-810G, Method 511.5, Procedure I	Pass
Vibration: General Vibration – operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Panasonic provided conditions (operating) 	Pass
Vibration: General Vibration – non-operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Category 24, general minimal integrity (non-operating) 	Pass
Vibration: General Vibration – operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Category 24, helicopter minimal integrity (operating), 2 hours per axis 	Pass
Vibration: General Vibration – non-operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Category 24, helicopter minimal integrity (non-operating), 1 hour per axis 	Pass
Shock: Functional	MIL-STD-810G, Method 516.6, Procedure I <ul style="list-style-type: none"> 40g, 11ms Operating 	Pass

Test Description	Test Parameters	Test Results
Shock: Transit-Drop 48-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 48in height on to 2in plywood – operating • All drops performed on the same unit • All drop heights performed on the same unit 	Pass
Shock: Transit-Drop 60-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 60in height on to 2in plywood – operating • All drops performed on the same unit • All drop heights performed on the same unit 	Pass
Shock: Transit-Drop 72-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 72in height on to 2in plywood – operating • All drops performed on the same unit • All drop heights performed on the same unit 	Pass
Freeze / Thaw	MIL-STD-810G, Method 524, Procedure III (Rapid Temperature Change) <ul style="list-style-type: none"> • Test effects include condensation 	Pass